


Ice makers modular systems



cubers - flakers

Competitively priced modular ice makers manufactured to the highest specifications.

Modular - ice cubers



DC 90A



DC 155A



DC 300A

Icemaker Model	Production Kgs - 24hrs	Dimensions mm			Consumption		Weight Kgs Net	Suits Bin/s				
		Width	Depth	Height	Electricity Kw	Water Ltr/Kg						
DC 90A	90	862	470	620	0.85	2.20	83	B400	-	B450	B530	-
DC 155A	155	862	555	720	1.40	2.60	118	B400	B850	B450	B530	RB280
DC 300A	300	1250	580	818	2.60	2.60	152	-	B850	-	-	RB280

Modular ice cubers - vertical evaporator




DCV 140A



DCV 225A



DCV 415A



Icemaker Model	Production Kgs - 24hrs	Dimensions mm			Consumption		Weight Kgs Net	Suits Bin/s				
		Width	Depth	Height	Electricity Kw	Water Ltr/Kg						
DCV 140A	140	540	544	707	1.40	2.80	85	B400	-	B450	B530	-
DCV 225A	225	770	550	740	1.55	1.90	90	B400	B850	B450	B530	RB280
DCV 415A	415	770	550	740	2.70	1.50	113	B400	B850	B450	B530	RB280

- 30 years manufacturing experience has given us the ultimate design in ice production technology
- Non-corrosive quality components for reliability, including tin-plated evaporator units to inhibit the formation of limescale
- Constructed of food quality stainless steel for strength and hygiene
- Environmentally friendly refrigerant R404
- Fully insulated storage bins made from non-toxic moulded ABS plastic for easy cleaning
- Water-cooled icemakers available on request
- Complies with WRC regulations on water consumption and direct connection to mains supply
- Sparkling ice made at minus 25°C lasts longer in the storage bin, and in your ice bucket
- One year parts and labour warranty



Modular ice flakers - granular



DCG 250A



DCG 500A



DCG 1000A

Icemaker Model	Production Kgs - 24hrs	Dimensions mm			Consumption		Weight Kgs Net	Suits Bin/s					
		Width	Depth	Height	Electricity Kw	Water Ltr/Kg		B400	B850	B450	B530	RB140	RB280
DCG 250A	250	640	470	687	1.05	1.00	82	B400	B850	B450	B530	RB140	-
DCG 500A	500	640	470	704	1.70	1.00	104	B400	B850	B450	B530	RB140	RB280
DCG 1000A	1000	934	684	700	3.70	1.00	172	-	-	-	-	-	RB280

Modular ice flakers



DCF 320A



DCF 850A

Icemaker Model	Production Kgs - 24hrs	Dimensions mm			Consumption		Weight Kgs Net	Suits Bin/s	
		Width	Depth	Height	Electricity Kw	Water Ltr/Kg		B850	RB280
DCF 320A	320	900	588	705	2.10	1.00	127	B850	RB280
DCF 850A	850	1107	700	880	4.60	1.00	290	B850	-

Production Figures: based on 20°C ambient temperature and 15°C water temperature.

Connection Requirements: water inlet 3/4", waste 24mm gravity.

Power Requirements: 13 amps, 240 volts (models DCG 1000A and DCF 850A require 20-30 amps).

In order to keep maintenance costs to a minimum, we recommend that replaceable scale reducer/filter cartridges are installed with your icemaker, especially in hard water areas.

Modular ice bins - fully insulated



B 400



B 850



B 530

Bin Model	Bin Capacity Kgs			Dimensions mm				Waste Height max	Weight Kgs Net	Suits Production Unit/s							
	Cubes	Flakes	Granular	Width	Depth	Height + legs	DC90			DC155	-	DCV	DCG250	DCG500	-	-	
B 400 S.Steel	180	-	120	862	840	850	150	150	64	DC90	DC155	-	DCV	DCG250	DCG500	-	-
B 850 S.Steel	380	400	280	1250	900	1000	150	150	104	-	DC155	DC300	DCV	DCG250	DCG500	DCF320	DCF850
B 450 Plastic**	200	-	160	862	770	1050	150	150	43	DC90	DC155	-	DCV	DCG225	DCG500	-	-
B 530 Plastic	240	-	190	942	796	1053	150	150	61	DC90	DC155	-	DCV	DCG250	DCG500	-	-

B 400 & B 850 bins can be dismantled and reassembled for situations where access is tight. B 450** not illustrated.

Modular roller bins



RB 140



RB 280

Bin Model	Bin Capacity Kgs			Dimensions mm			Tap Height max	Weight Kgs Net	Suits Production Unit/s						
	Cubes	Flakes	Granular	Width	Depth	Height			DC155	DC300	DCG250	DCG500	DCV225	DCV415	DCF320
RB 140	108+17*	-	90+14*	795	970	1285	250	64	-	-	DCG250	DCG500	-	-	-
RB 280	216+50*	216+50*	174+40*	1560	970	1485	250	135	DC155	DC300	DCG250	DCG500	DCV225	DCV415	DCF320

* Reserve capacity contained in chute when bin not in situ.

DC SERIES
ICEMAKING SYSTEMS

Direct Catering Products
Northload House, Northload Lane
Theale, Wexmore, Somerset BS28 4SY
Telephone: 01934 713358
Fax: 01934 712164

www.directcateringproducts.co.uk
E-mail: sales@directcateringproducts.co.uk

For larger capacity machines please refer to our Modular Systems Brochure



Authorised Dealer